

Status Page

MFP

ECOSYS M4132idn



RCT2Z02091

2023/02/10 14:19

[2.1.8] [2P1_F000.002.003]

Firmware Version 2P1_S000.002.403 2022.06.15

[2P1_1000.003.101] [2P1_1100.001.002] [2P1_7000.002.403]

Paper Settings

MP Tray Size/Type: A4/Plain
Cassette 1 Size/Type: A4/Plain
Cassette 2 Size/Type: A4-R/Plain

Group Settings

None

Print Settings

Copies: 1
Default Media Type: None
KIR Mode: Enabled
Resolution: 600 dpi

EcoPrint

Status: Disabled

Device Common Settings

Sleep Level: Energy Saver
Application: Enabled
Sleep Timer: 1 Minutes
Form Feed Time Out: 30 Seconds
MP Tray Empty: Enabled

Option Status

Paper Feeder: Cassette (500)
Finisher: Not Installed
SD Card: Not Installed
SSD: Not Installed
Card Authentication (B): Not Installed
Data Security Kit (E): Not Installed
UG-33: Not Installed
Scan extension kit(A): Not Installed

Network

LAN Interface

Setting: Auto
Current: 1000BASE-T

TCP/IP

Status: Enabled
Printer Host Name: KME49276

IPv4

DHCPv4 Status: Disabled
Bonjour Status: Enabled
IP Address: 192.168.0.88
Subnet Mask: 255.255.255.0
Default Gateway: 192.168.0.1

IPv6

Status: Disabled
DHCPv6 Status: Enabled
RA Status: Enabled
Manual: Not Defined
DHCPv6(Stateful): Not Defined
RA(Stateless): Not Defined
LinkLocal: Not Defined

JOB Settings

JOB Name: doc

Interface Block

USB Host: Unblock
USB Device: Unblock
USB Storage: Unblock
Option I/F 1: Unblock
Option I/F 2: Unblock

Memory

Standard Size: 1.0 GB
Option Slot: 0 MB
Total Size: 1.0 GB
RAM Disk: On
RAM Disk Size: 128 MB

Emulation

Emulation: PCL6
Default Font: Courier
Default Code Set: IBM PC-8

Scan Settings

File Format: PDF
Resolution: 300x300dpi
Quality: Text+Photo

Copy Settings

Quality: Text+Photo
Collate: Enabled

Counters

Copy 569
Printer 1185
FAX 0

Total 1754

Paper Size

A3 0
B4 0
A4 1754
B5 0
A5 0
Folio 0
Ledger 0
Legal 0
Letter 0
Statement 0
Other1 0
Other2 0

Scanned Pages

Copy 248
FAX 0
Other 97

Total 345

Duplex 114 Simplex 1640 2 in 1 8 4 in 1 0 1 in 1 1746

Data Sanitization

Result:--

Toner Gauge

